


HYUNDAI

POWER EQUIPMENT

Diesel Generator
Standby Power 33KVA
3 Phase 1500 rpm
DHY34KE
DHY34KSE



All Days | Safty | Reliable | Stability



TECHNICAL SPECIFICATION

DHY34KE OPEN TYPE / DHY34KSE CANOPY TYPE

50Hz
Standby 33KVA

Benefits and Feature

- > Use best quality vehicle engine, low fuel consumption, running reliable
- > Use high quality and performance brushless alternator, with AVR
- > High quality controller of COMAP/ DEESEA
- > Block design electrical control system, easy operate and maintenance
- > Standard 8 hours generator running base frame fuel tank (100% load)
- > With baseframe fork lift hole and generator canopy lifting hole
- > Industrial waterproof canopy, ensure generator all days running
- > Industrial silencer (7 meters the noise is lower than 68 dB)
- > Easy operation , IP23 protection industrial sockets and plugs
- > Four pole circuit breaker with RCD earth protection
- > Standard ATS function connector

Technical Specification

Prime Power	KVA/ KW	30 / 24
Standby Power	KVA/ KW	33 / 26.4
Power Factor		0.8
Frequency	Hz	50
Rate Voltage	V	400/230
Rate Current	A	47.6
Controller	COMAP/DEESEA	
Control Voltage	DC / V	12
Battery Capacity	Ah	60
Coolant Capacity	L	5.2
Fuel Tank Capacity(Base frame)	L	75
Fuel Consumption	L/hour	8.76
Running Time	Hour	10.8

Voltage

Steady state regulation	%	$\leq \pm 0.5$
Dynamic voltage renewal	%	$\leq +20 \sim -15$
Stable time	Sec	2.0
Waveform distortion		≤ 3
Volatility		≤ 0.5

Frequency

Steady state regulation	%	$\leq \pm 1$
Dynamic frequency renewal	%	$\leq +10 \sim -7$
Stable time	Sec	≤ 3
Volatility		≤ 0.5

Environment require

Temperature	C	≤ 40
Humidity	%	≤ 60
Altitude	m	≤ 1000

Standard

ISO3046, ISO8528, ISO9001-2008

Dimension | Weight | Sound



DHY34KE OPEN TYPE

Length	mm	1950
Width (W)	mm	820
Height (H)	mm	1080
Weight net	Kg	790
loading capacity (units/container)		
Sound @7 meter	dB	92



DHY34KSE CANOPY TYPE

Length	mm	2100
Width (W)	mm	900
Height (H)	mm	1400
Weight net	Kg	900
loading capacity (units/container)		
Sound @7 meter	dB	68

Note

1. Generator continuous running at variable load for unlimited periods with 10% overload available for 1 hour in any 12 hours period
2. Every generator strictly test on 0%, 25%, 75%, 100%, 110% load dynamic responsiveness ability, and all protections



DIESEL ENGINE

Model		HY4102
Prime power	Kw	32
Structure		4 cylinder, inline
Fuel type		Diesel
Fuel consumption	L/Hour	8.76.
Lubricant consumption	L/Hour	0.047
Governor		Electronic
Cooling		Water
Lubricant capacity	L	8
Air intake flow	m ³ /min	2.5
Exhaust gas flow	m ³ /min	7
Exhaust gas temperature	°C	460
Exhaust gas back pressure	KPa	6.7
Compression ratio		17
Aspiration		Turbocharged
Bore	mm	90
Stroke		100
Displacement	L	2.54
SAE		3/10
Dimension	mm	870 × 622 × 730
Net weight	Kg	320

Powerful engine and reliable running quality

Durable running performance and was proofed by vehicle's application

Compact structure

Compact structure and metal materials saving for low cost


Low maintenance and repair cost

Air, fuel and oil tubes are silicone and stainless steel materials, which reduce leakage problems substantially

Excellent start performance

Fuel injector and pump were tested fully in Various environments, which provide excellent start and running performance

ALTERNATOR



Model		184G
Prime power	kVA	31
Structure		1 bearing
Excitation mode		Self-excitation
Insulation class		H
Protection class		IP23
TIF		<50
THF		<2%
Air flow	m ³ /s	0.096
AVR Model		SX460


Best structure
Excellent design ensures compact structure and perfect appearance

Excellent performance
Excitation enhanced system improves start and short circuit's protection performance

Economy
Less parts involved and the most market's demand lead to cheap price and fine quality

Easy maintenance and repair
Core parts won't be involved in repair job, AVR can be replaced easily, examining diode doesn't disassemble rotor.

CONTROL PANEL



Controller

Comap AMF20

Support engine and alternator monitoring, measurement and protection. This is long-running and back-up unit to integrate the best way to control, support Modbus standard, modem, RS485, USB and internet.

Deepsea DSE6120



DSE6110/20 MKIII
AUTO START & AUTO MAINS (UTILITY)
FAILURE CONTROL MODULES

Measurement, displayment

Genset prime power Kw	●
Power factor	●
Engine speed	●
Phase to neutral voltage	●
Phase to phase voltage	●
Genset frequency	●
Genset current	●
Mains Phase to neutral voltage	○
Mains Phase to phase voltage	○
Mains frequency	○
Engine oil pressure	●
Engine water temperature	●
Fuel level	●
Battery voltage	●
Genset power KVA	●
Genset running time	●
Genset output KWh	●
History file	●

Alarm, shutdown function


Low oil pressure warning, shutdown	●
High water temperature warning, shutdown	●
Engine over and under speed shutdown	●
Low fuel level warning, shutdown	●
Battery low and high voltage warning	●
Battery charging failure	●
Genset low and high voltage warning, shut down	●
Alternator 3 phase voltage unbalance shut down	●
Alternator low and high frequency warning, shut down	●
Genset over load shutdown	●
Alternator 3 phase current unbalance shutdown	●
Mains low and high voltage warning	○
Mains low and high frequency warning	○

Optional

Remote start and stop	●
RS232 card	x
USB card	●
RS485 card	○
Multi language display	○
GPRS communication	○
GPS communication	○

● standard ○ optional x None

ACCESSORIES



Exhaust system



Residential muffler

Exhaust gas pipe

Preheating system



Water preheater

Oil preheater

alternator Anti-condensation heater

Fuel system



Auto filling fuel pump

Manual filling fuel pump

500L base frame fuel tank

1000L base frame fuel tank

500L External fuel tank

1000L External fuel tank

Electrical system



AMF20 controller

IC-NT
synchronizing
controller

wireless remote starter

Maintenance spare parts



500 hours genset spare parts

1000 hours genset spare parts